



# Specialty Hose & Tubing



P.O. Box 1224

Manchester, NH 03105

Ph. 603-497-5941

Fx. (603) 497-5853

## ASH-5000 **Recommended:** For bulk loading of ammonium-nitrate-fuel oil blasting agents in small diameter holes.

MSHA Accepted ( MSHA#IC-157/1 )  
For Use Underground

### Feature

Anti-Static PVC Compound With Continuous Yellow Stripe

### Function / Benefit

Effectively limits build-up of static electricity and provides a path for its safe dissipation to ground.

Ample conductance to bleed off static charges built up during pneumatic loading of AN/FO mixtures.

Sufficient resistance to guard blasting circuit against stray electrical currents.

Good wear resistance.

Sufficient flexibility to handle easily, yet rigid enough to reach upwards into collars of steeply inclined holes.

Makes hose easily identifiable in underground lighting.

### Specifications

Inside diameter		Outside diameter		Max. W.P. PSI	Coil Length	
Inches	mm	Inches	mm		FT	M
.500	13	.750	19	125	100	30
.750	19	.940	24	100	100	30
.800	20	1.100	28	125	100	30
1.000	25	1.250	32	100	100	30
1.000	25	1.350	34	125	100	30

Other sizes are available for quotation -  
Rigid anti-static pipe (10 ft lengths) also available